

WATERPROOFS

PRIMERS

A collection of various water droplets and splashes in shades of blue and white, scattered across the page.

PRODUCT DATA SHEET

PRIMER TYPE A



WATERPROOFS
Vergroothandel Van der Kooij
Oude Medelsestraat 18-C
4005 EK Tiel
Nederland
+31 344 62 44 11
info@vanderkooy.nl

PRODUCT DATA SHEET

PRIMER TYPE A

DESCRIPTION

Colourless impregnating primer based on acrylic hydrosols.

MAIN PROPERTIES

High fixing capacity.

RECOMMENDED USES

On different porous and chalking substrates, before painting them with waterborne paints.

TECHNICAL DATA

Appearance:	Glossy (gloss 60°: ± 80%)
Colour:	Colourless
Density:	1,0 g/cm ³
Solids Content:	In volume: 14 - 16% In weight: 14 - 16%
Recommended film thickness:	Wet film: 100 micron (consumption: 10 m ² /l) Dry film: 15 micron (consumption: 10 m ² /l)
Flashpoint:	Not flammable
VOC-content:	0 g/l max.
Ready-to-use-mixture:	0 g/l max.
Category:	A/g
UE Limit values:	50 g/l (2007) / 30 g/l (2010)
Drying times:	20°C/50% r.h.
To touch:	1 hour
To handle:	4 hour
To recoat:	2 - 4 hours, depending of the consumption
Full hardness:	± 24 hours

COVERAGE

Very porous substrates (concrete, bricks): 5 - 10 m²/l

Little porous substrates (plaster, porous paints for inside use): 15 - 20 m²/l.

SURFACE PREPARATION

Remove dust and / or clean carefully.

Blistering plaster has to be sanded slightly to ensure a good adhesion or an adhesion test has to be done in advance.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

WATERPROOFS
PRIMERS

PRODUCT DATA SHEET

PRIMER TYPE A

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION ET DILUTION

Brush:	Apply undiluted.
Roller:	Apply undiluted.
Air-atomised spray:	Apply undiluted.
Airless spray:	Nozzle: 11 – 15. Pressure: 200 bars. Apply undiluted.
Cleanup:	Water

APPLICATION CONDITIONS

Minimum 5°C and maximum 90 % R.H.

REMARKS

On low porosity substrates, WATERPROOFS Primer Type A is preferred above Primer Type C because of its better penetration characteristics.

Possible dried spots (on windows, floors, etc.) can be removed with thinner.

When using on chalking substrates, always test for fixing suitability.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° et 35°C.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

WATERPROOFS
PRIMERS