

WATERPROOFS

PRIMERS

A collection of various water droplets and splashes in shades of blue and white, scattered across the page. Some are large and clear, while others are smaller and more misty.

PRODUCT DATA SHEET

PRIMER TYPE B



WATERPROOFS
Verfgroothandel Van der Kooij
Oude Medelsestraat 18-C
4005 EK Tiel
Nederland
+31 344 62 44 11
info@vanderkooy.nl

PRODUCT DATA SHEET

PRIMER TYPE B

DESCRIPTION

Ready to use solvent based fixing primer based on chlorinated rubber.

MAIN PROPERTIES

Large fixation capacity for stabilizing loose particles – improves the adherence of subsequent topcoats – unsaponifiable – good UV-resistance – flexible

RECOMMENDED USES

Fixation layer for porous and unpainted mineral substrates.

TECHNICAL DATA

Appearance:	Glossy (gloss 60°: ± 90%)
Colour:	Grey
Density:	1,07 - 1,11 g/cm ³
Solids Content:	In volume: 30 - 34% In weight: 43 - 47%
Recommended film thickness:	Wet film: 70 micron (consumption: 14 m ² /l) Dry film: 23 micron (consumption: 14 m ² /l)
Flashpoint:	41°C
VOC-content:	599 g/l max.
Ready-to-use-mixture:	599 g/l max.
Category:	A/h
UE Limit values:	750 g/l (2007) / 750 g/l (2010)
Drying times:	20°C/50% r.h.
To touch:	1 hour
To handle:	1 hour
To recoat:	24 hours
Full hardness:	24 hours

COVERAGE

Theoretical:	14 m ² /l
Practical:	10 - 15 m ² /l. Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

SURFACE PREPARATION

Clean and degrease the substrate. If the substrate is an acrylic paint, this must NOT be recoated with WATERPROOFS Primer Type B (the acrylic paint is affected by the solvents of Primer Type B). In such a case, replace Primer Type B with Primer Type A.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

WATERPROOFS
PRIMERS

PRODUCT DATA SHEET

PRIMER TYPE B

DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.

APPLICATION ET DILUTION

Brush:	All types. Do not dilute.
Roller:	All types. Do not dilute.
Air-atomised spray:	Do not dilute.
Airless spray:	Do not dilute. Nozzle: 011 – 013. Pressure: 150 - 170 bars.
Cleanup:	Thinner

APPLICATION CONDITIONS

Apply in a dry and well-ventilated area.

REMARKS

- Ready for use. Do not dilute.
- Reversible paint system, this means that the product dissolves in its own solvent.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° et 35°C.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

WATERPROOFS
PRIMERS