

# WATERPROOFS

# PRIMERS

A collection of various water droplets and splashes in shades of blue and white, scattered across the page. Some are large and clear, while others are smaller and more misty. They are positioned around the central text.

# PRODUCT DATA SHEET

## PRIMER TYPE C



WATERPROOFS  
Vergroothandel Van der Kooij  
Oude Medelsestraat 18-C  
4005 EK Tiel  
Nederland  
+31 344 62 44 11  
[info@vanderkooy.nl](mailto:info@vanderkooy.nl)

# PRODUCT DATA SHEET

## PRIMER TYPE C

### DESCRIPTION

Colourless fixation primer based on acrylic dispersions for weathered bituminous substrates.

### RECOMMENDED USES

Fixation coat on weathered bituminous surfaces before recoating with WATERPROOFS Roofing Coating.

### TECHNICAL DATA

Appearance:	Glossy (gloss 60°: ± 90%)
Colour:	Colourless
Density:	1,0 g/cm <sup>3</sup>
Solids Content:	In volume: 27 - 29% In weight: 27 - 29%
Recommended film thickness:	Wet film: 100 micron (consumption: 10 m <sup>2</sup> /l) Dry film: 28 micron (consumption: 10 m <sup>2</sup> /l)
Flashpoint:	Not flammable
VOC-content:	40 g/l max.
Ready-to-use-mixture:	40 g/l max.
Category:	A/i
UE Limit values:	140 g/l (2007) / 140 g/l (2010)
Drying times:	20°C/50% r.h.
To touch:	1 1/2 hour
To handle:	4 hours
To recoat:	1 day
Full hardness:	1 week

### COVERAGE

Theoretical:	5 - 10 m <sup>2</sup> /l
Practical:	Practical coverage depends on many factors such as porosity and roughness of the substrate and material losses during application.

### SURFACE PREPARATION

Do not apply on fibre cement boards: use WATERPROOFS Primer Type B in this case. Do not apply on low porous substrates like plaster, use Primer Type A.

### DIRECTION FOR USE

To ensure homogeneity, coating materials should be thoroughly stirred prior to use.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

**WATERPROOFS**  
PRIMERS

# PRODUCT DATA SHEET

## PRIMER TYPE C

### APPLICATION ET DILUTION

Brush:	Apply undiluted.
Roller:	Apply undiluted.
Air-atomised spray:	Dilute with water.
Airless spray:	Apply undiluted. Nozzle: 011 – 015. Pressure: 180 - 200 bars.
Cleanup:	Water

### APPLICATION CONDITIONS

Minimum 5°C - Maximum 80% R.H.

### SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

### SHELLIFE / STORAGE CONDITIONS

2 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° et 35°C.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

**WATERPROOFS**  
**PRIMERS**