

WATERPROOFS

THINNER

A collection of various water droplets and splashes in shades of blue and white, scattered across the page. Some are large and clear, while others are smaller and more misty. They are positioned around the central text.

PRODUCT DATA SHEET

THINNER



WATERPROOFS
Verfgroothandel Van der Kooij
Oude Medelsestraat 18-C
4005 EK Tiel
Nederland
+31 344 62 44 11
info@vanderkooy.nl

PRODUCT DATA SHEET

THINNER

DESCRIPTION

Solvent based on aromatic hydrocarbons.

MAIN PROPERTIES

Strong dilution capacity.

RECOMMENDED USES

Dilution of synthetic enamels and varnishes for airless application. Degreasing of metals and most wood types. Cleaning of 'spots' of acrylic paints or acrylic fixing paints (e.g. on glass).

TECHNICAL DATA

Colour:	Colourless
Density:	0,87 g/cm ³
VOC-content:	1150 g/l
Flashpoint:	>41°C
Boiling range:	160 - 180°C
Kb-value:	>90
Aromatic content:	>99%

INSTRUCTIONS FOR USE

WATERPROOFS Thinner is the only appropriated dilution solvent for WATERPROOFS Primer Type B.

On substrates that are attacked by Thinner (e.g. glass, stoving enamel), spots of acrylic impregnation products (e.g. Primer Type A, Primer Type C) and acrylic paints can be easily removed with a rag soaked in Thinner.

SAFETY

Consult Safety Data Sheet and Safety Information printed on the can.

SHELLIFE / STORAGE CONDITIONS

5 years from date of production in unopened cans, if stored in dry, well ventilated areas, not in direct sunlight at temperatures between 5° et 35°C.



The information contained herein is given in good faith. However, since application conditions are beyond our control, WATERPROOFS cannot assume responsibility for any risks or liabilities which may result from the use of these products. The company reserves the right to modify data without prior notice.

WATERPROOFS
THINNER